

Antiferroelectric materials, which exhibit high saturation polarization intensity with small residual polarization intensity, are considered as the most promising dielectric energy storage materials. The energy storage properties of ceramics are known to be highly dependent on the annealing atmosphere employed in their preparation. In this study, we investigated the ...

From core-shell Ba_{0.4} Sr_{0.6} TiO₃@SiO₂ particles to dense ceramics with high energy storage performance by spark plasma sintering. *J. Mater. Chem. A* 6, 4477-4484 (2018).

This paper first briefly introduces the basic physical principles and energy storage performance evaluation parameters of dielectric energy storage materials, then summarizes the critical research systems and related progress of BNT-based lead-free energy storage materials (bulk ceramics, films and multilayer ceramics) from the aspects of ions ...

The pore size and structure of MOF-derived ceramics can be tailored through synthesis parameters, allowing for optimization of ion diffusion kinetics and energy storage capacity. These ceramics exhibit enhanced chemical stability compared to the parent MOF materials, ensuring long-term performance and durability in energy storage applications.

This paper is based on ceramic capacitors with high energy storage performance, a series of high-entropy perovskite oxide ceramics designed by the concept of "entropy engineering" in the past five years are reviewed. ... Multi-scale collaborative optimization of SrTiO₃-based energy storage ceramics with high performance and excellent stability ...

Environment-friendly Ba_{0.95}Ca_{0.05}Ti_{0.91}Sn_{0.09-x}Zr_xO₃ ceramics, with $x = 0.00$ and 0.01 (BCTSZ_x) were prepared through a standard solid-state sintering process. The diffusion coefficient estimated from the Santos-Eiras fit of $\epsilon_r - T$ plot implies that the ferroelectric-paraelectric transition is a diffuse type. Well-saturated and fatigue ...

This work demonstrates remarkable advances in the overall energy storage performance of lead-free bulk ceramics and inspires further attempts to achieve high-temperature energy storage properties ...

However, the low polarizability and high remnant polarization of the existing transparent dielectric ceramics limit the promotion of energy storage performance. Here, Bi(Li_{0.5} Nb_{0.5})O₃ (BLN) was chosen to modify the (K ...

BaTiO₃ ceramics are difficult to withstand high electric fields, so the energy storage density is relatively low, inhabiting their applications for miniaturized and lightweight power electronic devices. To address this issue,

we added Sr 0.7 Bi 0.2 TiO₃ (SBT) into BaTiO₃ (BT) to destroy the long-range ferroelectric domains. Ca²⁺ was introduced into BT-SBT in the ...

In addition, the prepared ceramics exhibit extremely high discharge energy density (4.52 J cm⁻³) and power density (405.50 MW cm⁻³). Here, the results demonstrate that the strategy of layered structure design and optimization is promising for enhancing the energy storage performance of lead-free ceramics.

For example, Z. Wang et al. [63] investigated the effects of Sr/Ti ratio on the microstructure and energy storage performance of ST ceramic. They observed that the grain size tends to first increase and then decrease with an increasing Sr/Ti ratio, reaching the highest W_{rec} of 1.21 J cm⁻³ under 283 kV cm⁻¹ when Sr/Ti = 0.996. Z.

This work employs the conventional solid-state reaction method to synthesize Ba_{0.92}La_{0.08}Ti_{0.95}Mg_{0.05}O₃ (BLMT5) ceramics. The goal is to investigate how defect dipoles affect the ability of lead-free ferroelectric ceramics made from BaTiO₃ to store energy. An extensive examination was performed on the crystal structure, dielectric properties, and ...

Recently, lead-free dielectric capacitors have attracted more and more attention for researchers and play an important role in the component of advanced high-power energy storage equipment [[1], [2], [3]]. Especially, the country attaches great importance to the sustainable development strategy and vigorously develops green energy in recent years [4].

An energy storage density of 2.2 J/cm³ and efficiency of 73.2% was obtained in CBT28. The BDS of BST-BNT ceramics was significantly improved by Ca_{0.85}Bi_{0.1}TiO₃ optimized. BST-BNT ceramics modified with Ca_{0.85}Bi_{0.1}TiO₃ exhibits strong relaxation behavior. Composition modification is a feasible way to improve the energy storage of ceramics.

Exploring high-performance energy storage dielectric ceramics for pulse power applications is paramount concern for a multitude of researchers. In this work, a (1 - x)K_{0.5}Na_{0.5}NbO_{3-x}Bi_{0.5}La_{0.5}(Zn_{0.5}Sn_{0.5})O₃ ((1-x)KNN-xBLZS) lead-free relaxor ceramic was successfully synthesized by a conventional solid-reaction method. X-ray diffraction and Raman ...

There is an urgent need to develop stable and high-energy storage dielectric ceramics; therefore, in this study, the energy storage performance of Na_{0.5-x}Bi_{0.46-x}Sr_{2x}La_{0.04}(Ti_{0.96}Nb_{0.04})O_{3.02} (x = 0.025-0.150) ceramics prepared via the viscous polymer process was investigated for energy storage. It was found that with increasing Sr²⁺ content, the material ...

The KNN-H ceramic exhibits excellent comprehensive energy storage properties with giant W_{rec} , ultrahigh i , large H_v , good temperature/frequency/cycling stability, and ...

A new strategy for achieving excellent energy storage property of NN-based ceramics was proposed. A

modified two-step sintering method is employed to sustain the high P_{max} of BNT under low electric f...

Bismuth sodium titanate ($\text{Bi}_{0.5}\text{Na}_{0.5}\text{TiO}_3$, BNT) based ferroelectric ceramic is one of the important lead free dielectric materials for high energy storage applications due to its large polarization. Herein, we reported a modified BNT based relaxor ferroelectric ceramics composited with relaxor $\text{Sr}_{0.7}\text{Bi}_{0.2}\text{TiO}_3$ (SBT) and ferroelectric BaTiO_3 (BT), which exhibits a ...

Lead-free bulk ceramics for advanced pulse power capacitors possess low recoverable energy storage density (W_{rec}) under low electric field. Sodium bismuth titanate ($\text{Bi}_{0.5}\text{Na}_{0.5}\text{TiO}_3$, BNT)-based ferroelectrics have attracted great attention due to their large maximum polarization (P_m) and high power density. The BNT-ST: $x\text{AlN}$ ceramics are ...

Lead-free ceramics with excellent energy storage performance are important for high-power energy storage devices. In this study, $0.9\text{BaTiO}_3\text{-}0.1\text{Bi}(\text{Mg}_{2/3}\text{Nb}_{1/3})\text{O}_3$ (BT-BMN) ceramics with x wt% $\text{ZnO-Bi}_2\text{O}_3\text{-SiO}_2$ (ZBS) ($x = 2, 4, 6, 8, 10$) glass additives were fabricated using the solid-state reaction method. X-ray diffraction (XRD) analysis revealed that the ZBS ...

Barium Titanate ceramics are widely used in capacitor field due to their high dielectric constant and low dielectric loss. However, their low energy storage density limits the application in high energy density energy storage devices [8, 9]. To improve energy storage performance, researchers introduce ion doping in recent years, which is a commonly used ...

For the Pb-free energy storage ceramics, Guo et al. investigated the Pb-doped $(\text{Bi,Na,Sr})\text{TiO}_3$ ceramics [19] and the $(\text{Bi,Na,Ba,Sr,Ca})\text{TiO}_3$ high-entropy ceramics [20], taking advantage of hybridization between O ions and Pb ions to improve the P_m , coupled with the utilization of a sintering aid factor of Pb to improve microstructure. As ...

The optimum electric field strengths applied during crystallization, namely 2 and 3 kV cm^{-1} , can achieve much better energy storage densities with high efficiencies of 10.36 J cm^{-3} with 85.8% and 12.04 J cm^{-3} with 81.1%, respectively, which represents a very strong energy storage performance compared to many dielectric ceramics so far ...

Energy storage performance of $\text{Na}_{0.5}\text{Bi}_{0.5}\text{TiO}_3$ based lead-free ferroelectric ceramics prepared via non-uniform phase structure modification and rolling process Author links open overlay panel Biao Guo a, Yan Yan a, Mingyang Tang a, Ziyang Wang b, Yang Li a, Leiyang Zhang c, Haibo Zhang d, Li Jin c, Gang Liu a

Compared to lead-based ceramics, lead-free dielectric ceramics have lower density ($\approx 5.5 \text{ g/cm}^3$), which makes it easier to meet the requirements for lightweight of energy storage capacitors for pulse power equipment as energy storage materials [13], [14], [15]. However, due to the low saturation polarization intensity (P_{max}) of lead-free ceramics, ...

As the industrial pillar of electronic ceramics, BaTiO₃ ceramic is difficult to achieve large energy storing performance due to its high P_r and low dielectric breakdown field strength, making it difficult to satisfy their development requirements of miniaturization and lightweight of power electronic equipment. Therefore, a two-step strategy including adjusting ...

However, the low polarizability and high remnant polarization of the existing transparent dielectric ceramics limit the promotion of energy storage performance. Here, Bi(Li_{0.5}Nb_{0.5})O₃ (BLN) was chosen to modify the (K_{0.5}Na_{0.5})NbO₃ (KNN)-based ceramics to optimize the optical transmittance and energy storage characteristics simultaneously.

Over the past decades, Na_{0.5}Bi_{0.5}TiO₃ (NBT)-based ceramics have received increasing attention in energy storage applications due to their high power density and relatively large maximum polarization. However, their high remnant polarization (P_r) and low breakdown field strength are detrimental for their practical applications. In this paper, a new solid solution ...

Next-generation advanced high/pulsed power capacitors rely heavily on dielectric ceramics with high energy storage performance. However, thus far, the huge challenge of realizing ultrahigh ...

All this data encouraged us to develop a combinatorial optimization strategy to induce PNRs and enhance BDS to improve the energy-storage performance of the resulting ceramic materials (see Fig. 1). One of approaches is introducing ions with different radii and valences (such as Bi³⁺, Mg²⁺, Zr⁴⁺, Zn²⁺, Nb⁵⁺, etc.) to the A- and B-sites of KNN to ...

Abstract Enhancing the efficacy of energy storage materials is crucial for advancing contemporary electronic devices and energy storage technologies. This research focuses on boosting the energy storage capabilities of BaTiO₃ ceramics through Mg²⁺ doping. Introducing Mg²⁺ ions into the BaTiO₃ lattice induces defects and grain boundary effects, ...

How to develop energy storage ceramics with large W_{rec} and high η is one of the focuses of research. In the modification process, researchers aim to improve the maximum polarization strength (P_{max}) and reduce the residual polarization strength (P_r) by introducing heterovalent ions [5], adjusting the polarization behavior [6], and improving the relaxation of ...

As a result, the $x = 0.12$ ceramic exhibited superior comprehensive energy storage performance of large E_b (50.4 kV/mm), ultrahigh W_{rec} (7.3 J/cm³), high efficiency η (86.3%), relatively fast charge-discharge speed ($t_{0.9} = 6.1$ ms) and outstanding reliability under different frequency, fatigue, and temperature, indicating that the BiFeO₃ ...

The authors improve the energy storage performance and high temperature stability of lead-free tetragonal tungsten bronze dielectric ceramics through high entropy strategy and band gap engineering.

To evaluate the overall energy-storage performance of these ceramics, we measured the unipolar P-E loops of these ceramics at their characteristic breakdown strength (Fig. 3E and fig. S13) and calculated the discharged energy densities U_e and energy-storage efficiency η (Fig. 3F and fig. S14).

Web: <https://shutters-alkazar.eu>

Chat online: <https://tawk.to/chat/667676879d7f358570d23f9d/1i0vbu11i?web=https://shutters-alkazar.eu>